Requirements of permit for Hot Tub/Spa -

- 1. Approved lockable safety cover (ASTM F 1346) or approved fence/gate
- 2. Must not be placed closer than five (5) feet to non-tempered glass
- 3. Do not place hot tub/spa under any existing overhead wires, or within 10ft. of wires
- 4. All receptacles within 20 feet of hot tub/spa must be GFCI protected
- 5. All metal parts must be bonded per the code requirements or meet manufacturers bonding requirements. No metal or metallic items within five (5) feet of hot tub/spa edge
- 6. Electrical disconnect must be within sight of hot tub/spa
- 7. No electrical equipment/devices within six (6) feet of hot tub/spa edge
- 8. Cannot be placed on a deck without engineering design
- 9. Installation must meet requirements of the International Swimming Pool & Spa Code and the International Residential Code

Wiring Requirements – (This list is not all inclusive)

- 1. All electric used in hot tub/spa installations must be in conduit/raceways and buried with the appropriate amount of fill.
- 2. Electric circuits that supply hot tubs/spas must be GFCI protected
- 3. Rigid Metal & Intermediate Medal conduit minimum burial depth is 6".
- 4. Nonmetallic raceways listed for direct burial minimum burial depth is 18".
- 5. Wiring in conduit/raceways must be suitable for wet or damp locations and have a individual insulated grounding conductor run with the line & neutral wires
- 6. All electrical work must meet the IRC and/or the NEC
- 7. DO NOT USE "UF" WIRING TO SUPPLY HOT TUB/SPA EQUIPMENT

The most recent editions of the International Codes as adopted by the state of Pennsylvania shall be used for compliance.